



# 2.6 VOC RAPTOR BEDLINER HARDENER - UP0827 / UP4824

## Safety Data Sheet RLHV-US - UP0827 / UP4824

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 08/13/2015 Version: 1.0

### DRIVING SURFACE PERFECTION

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

Product form : Mixtures  
 Product name : **2.6 VOC RAPTOR BEDLINER HARDENER - UP0827 / UP4824**  
 Product group : 2K Hardener

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.3. Details of the supplier of the safety data sheet

**Supplier**  
 U-POL US Inc  
 108 Commerce Way  
 Stockertown PA 18083 - USA  
 T 1-800-340-7824 - F 1-800-787-5150  
[technical.department@u-pol.com](mailto:technical.department@u-pol.com) - [www.u-pol.com](http://www.u-pol.com)

##### 1.4. Emergency telephone number

Emergency number : CHEMTREC - 1-800-424-9300 ( UK +44 (0) 1933 230310 (07:30 - 17:00hrs UK time) )

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### GHS-US classification

Flam. Liq. 2 H225  
 Skin Irrit. 2 H315  
 Eye Irrit. 2A H319  
 Skin Sens. 1 H317  
 STOT SE 3 H336  
 STOT SE 3 H335  
 STOT RE 2 H373

Full text of H statements : see section 16

##### 2.2. Label elements

###### GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H225 - Highly flammable liquid and vapor  
 H315 - Causes skin irritation  
 H317 - May cause an allergic skin reaction  
 H319 - Causes serious eye irritation  
 H335 - May cause respiratory irritation  
 H336 - May cause drowsiness or dizziness  
 H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS-US) :

P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking  
 P261 - Avoid breathing fume, spray, vapors  
 P280 - Wear face protection, protective clothing, protective gloves  
 P302+P352 - If on skin: Wash with plenty of water  
 P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 P312 - Call a POISON CENTER if you feel unwell

# 2.6 VOC RAPTOR BEDLINER HARDENER - UP0827 / UP4824

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS-US classification
HEXAMETHYLENE DIISOCYANATE OLIGOMERS	(CAS No) 28182-81-2	< 43	Acute Tox. 4 (Inhalation), H332 Skin Sens. 1, H317 STOT SE 3, H335
methyl acetate	(CAS No) 79-20-9	23 - 43	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
4-CHLORO BENZOTRIFLUORIDE	(CAS No) 98-56-6	5 - 23	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
xylene	(CAS No) 1330-20-7	5 - 23	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315
Solvent naphtha (petroleum), light arom.,		< 5	Flam. Liq. 3, H226 STOT SE 3, H336 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
ethylbenzene	(CAS No) 100-41-4	< 5	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Carc. 2, H351 STOT RE 2, H373 Asp. Tox. 1, H304

Full text of H-phrases: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Immediately call a poison center or doctor/physician. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention. Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. Repeated exposure may cause skin dryness or cracking.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries	: Causes damage to organs.
Symptoms/injuries after inhalation	: May cause an allergic skin reaction. May cause respiratory irritation. May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: Repeated exposure to this material can result in absorption through skin causing significant health hazard. Harmful in contact with skin. Causes skin irritation.
Symptoms/injuries after eye contact	: Causes serious eye irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

# 2.6 VOC RAPTOR BEDLINER HARDENER - UP0827 / UP4824

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.  
Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Highly flammable liquid and vapor.  
Explosion hazard : May form flammable/explosive vapor-air mixture.

#### 5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.  
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.

##### 6.1.1. For non-emergency personnel

- Protective equipment : Safety glasses. Protective clothing. Gloves.  
Emergency procedures : Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection. Avoid breathing spray, vapors.  
Emergency procedures : Ventilate area.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

- For containment : Contain released substance, pump into suitable containers. Collect spillage.  
Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

#### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection. For further information refer to section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.  
Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No open flames. No smoking. Use only non-sparking tools. Avoid breathing spray, vapors. Use only outdoors or in a well-ventilated area.  
Hygiene measures : Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

#### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical, Lighting equipment equipment.  
Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Ignition sources, Heat sources, Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep in fireproof place. Keep container tightly closed.  
Incompatible products : Strong bases. Strong acids.  
Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.  
Storage temperature : < 77°F  
Storage area : Store in a well-ventilated place.  
Special rules on packaging : Keep only in original container.

#### 7.3. Specific end use(s)

No additional information available

## 2.6 VOC RAPTOR BEDLINER HARDENER - UP0827 / UP4824

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### SECTION 8: Exposure controls/personal protection

##### 8.1. Control parameters

2.6 VOC RAPTOR BEDLINER HARDENER - UP0827 / UP4824		
ACGIH	Not applicable	
OSHA	Not applicable	
methyl acetate (79-20-9)		
ACGIH	ACGIH TWA (ppm)	200 ppm
ACGIH	ACGIH STEL (ppm)	250 ppm
ACGIH	Remark (ACGIH)	eye & URT irr
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	610 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	200 ppm
4-CHLORO BENZOTRIFLUORIDE (98-56-6)		
ACGIH	Not applicable	
OSHA	Not applicable	
ethylbenzene (100-41-4)		
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	Remark (ACGIH)	URT irr; kidney dam (nephropathy)
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
xylene (1330-20-7)		
ACGIH	ACGIH TWA (ppm)	100 ppm
ACGIH	ACGIH STEL (ppm)	150 ppm
ACGIH	Remark (ACGIH)	URT & eye irr; CNS impair
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
Solvent naphtha (petroleum), light arom.,		
ACGIH	Not applicable	
OSHA	Not applicable	
HEXAMETHYLENE DIISOCYANATE OLIGOMERS (28182-81-2)		
ACGIH	Not applicable	
OSHA	Not applicable	

##### 8.2. Exposure controls

Personal protective equipment

: Avoid all unnecessary exposure. Gas mask. Gloves. Protective clothing. Safety glasses.



Materials for protective clothing

: Impermeable clothing.

Hand protection

: Wear protective gloves.

Eye protection

: Chemical goggles or safety glasses.

Skin and body protection

: Wear suitable protective clothing.

Respiratory protection

: Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. Air-fed respiratory protective equipment should be worn when this product is sprayed.

Other information

: Do not eat, drink or smoke during use.

# 2.6 VOC RAPTOR BEDLINER HARDENER - UP0827 / UP4824

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Color	: Colorless
Odor	: aromatic
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: > 95°F
Flash point	: < 32°F
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Specific gravity / density	: 8.68 - 8.85 lb/gal
Solubility	: insoluble in water. soluble in most organic solvents.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available

#### 9.2. Other information

VOC content - As Packaged	: 128 g/l (1.07 lb/gal)
VOC content - As Applied	: With National Rule Raptor Bedliner Black - 211 g/l (1.76 lb/gal) With National Rule Raptor Bedliner Tintable - 195 g/l (1.63 lb/gal)

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No additional information available

#### 10.2. Chemical stability

Highly flammable liquid and vapor. May form flammable/explosive vapor-air mixture.

#### 10.3. Possibility of hazardous reactions

Not established.

#### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame.

#### 10.5. Incompatible materials

Strong acids. Strong bases.

#### 10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. May release flammable gases.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity	: Not classified
----------------	------------------

# 2.6 VOC RAPTOR BEDLINER HARDENER - UP0827 / UP4824

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>ethylbenzene (100-41-4)</b>	
ATE US (gases)	4500.000 ppmV/4h
ATE US (vapors)	11.000 mg/l/4h
ATE US (dust, mist)	1.500 mg/l/4h

<b>xylene (1330-20-7)</b>	
ATE US (dermal)	1100.000 mg/kg body weight
ATE US (dust, mist)	1.500 mg/l/4h

<b>HEXAMETHYLENE DIISOCYANATE OLIGOMERS (28182-81-2)</b>	
ATE US (gases)	4500.000 ppmV/4h
ATE US (vapors)	11.000 mg/l/4h
ATE US (dust, mist)	1.500 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.  
Serious eye damage/irritation : Causes serious eye irritation.  
Respiratory or skin sensitization : May cause an allergic skin reaction.  
Germ cell mutagenicity : Not classified  
Based on available data, the classification criteria are not met  
Carcinogenicity : Not classified

<b>ethylbenzene (100-41-4)</b>	
IARC group	2B - Possibly carcinogenic to humans

<b>xylene (1330-20-7)</b>	
IARC group	3 - Not classifiable

Reproductive toxicity : Not classified  
Based on available data, the classification criteria are not met  
Specific target organ toxicity – single exposure : May cause drowsiness or dizziness. May cause respiratory irritation.  
Specific target organ toxicity – repeated exposure : May cause damage to organs through prolonged or repeated exposure.  
Aspiration hazard : Not classified  
Potential Adverse human health effects and symptoms : Harmful in contact with skin. Based on available data, the classification criteria are not met.  
Symptoms/injuries after inhalation : May cause an allergic skin reaction. May cause respiratory irritation. May cause drowsiness or dizziness.  
Symptoms/injuries after skin contact : Repeated exposure to this material can result in absorption through skin causing significant health hazard. Harmful in contact with skin. Causes skin irritation.  
Symptoms/injuries after eye contact : Causes serious eye irritation.

## SECTION 12: Ecological information

### 12.1. Toxicity

No additional information available

### 12.2. Persistence and degradability

<b>2.6 VOC RAPTOR BEDLINER HARDENER - UP0827 / UP4824</b>	
Persistence and degradability	Not established.

<b>Solvent naphtha (petroleum), light arom.,</b>	
Persistence and degradability	May cause long-term adverse effects in the environment.

### 12.3. Bioaccumulative potential

<b>2.6 VOC RAPTOR BEDLINER HARDENER - UP0827 / UP4824</b>	
Bioaccumulative potential	Not established.

# 2.6 VOC RAPTOR BEDLINER HARDENER - UP0827 / UP4824

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Solvent naphtha (petroleum), light arom.,

Bioaccumulative potential	Not established.
---------------------------	------------------

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

Effect on ozone layer : No additional information available  
Effect on the global warming : No known effects from this product.  
Other information : Avoid release to the environment.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Regional legislation (waste) : Disposal must be done according to official regulations.  
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to Dispose in a safe manner in accordance with local/national regulations.  
Additional information : Handle empty containers with care because residual vapors are flammable.  
Ecology - waste materials : Avoid release to the environment.

### SECTION 14: Transport information

In accordance with DOT

Transport document description : UN1263 Paint related material (including paint thinning, drying, removing, or reducing compound), 3, II

UN-No.(DOT) : UN1263

Proper Shipping Name (DOT) : Paint related material including paint thinning, drying, removing, or reducing compound

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Hazard labels (DOT) : 3 - Flammable liquid

Packing group (DOT) : II - Medium Danger

DOT Special Provisions (49 CFR 172.102) : 149 - When transported as a limited quantity or a consumer commodity, the maximum net capacity specified in 173.150(b)(2) of this subchapter for inner packaging may be increased to 5 L (1.3 gallons).  
B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks.  
IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.  
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)  
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling =  $97 / 1 + a (tr - tf)$  Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.  
TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 C (32 F).  
TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150

DOT Packaging Non Bulk (49 CFR 173.xxx) : 173

DOT Packaging Bulk (49 CFR 173.xxx) : 242

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L

# 2.6 VOC RAPTOR BEDLINER HARDENER - UP0827 / UP4824

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

### Additional information

Other information : No supplementary information available.

### ADR

Transport document description : UN 1263 PAINT RELATED MATERIAL, 3, II, (D/E)  
Packing group (ADR) : II  
Class (ADR) : 3 - Flammable liquid  
Hazard identification number (Kemler No.) : 33  
Classification code (ADR) : F1  
Hazard labels (ADR) : 3 - Flammable liquids



Orange plates :



Tunnel restriction code (ADR) : D/E  
LQ : 5I  
Excepted quantities (ADR) : E2

### Transport by sea

UN-No. (IMDG) : 1263  
Proper Shipping Name (IMDG) : PAINT RELATED MATERIAL  
Class (IMDG) : 3 - Flammable liquids  
Packing group (IMDG) : II - substances presenting medium danger

### Air transport

UN-No. (IATA) : 1263  
Proper Shipping Name (IATA) : Paint  
Class (IATA) : 3 - Flammable Liquids  
Packing group (IATA) : II - Medium Danger

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

ethylbenzene	CAS No 100-41-4	< 5%
xylene	CAS No 1330-20-7	5 - 23%
hexamethylene-di-isocyanate	CAS No 822-06-0	< 5%

#### methyl acetate (79-20-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### 4-CHLORO BENZOTRIFLUORIDE (98-56-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### ethylbenzene (100-41-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Subject to reporting requirements of United States SARA Section 313

CERCLA RQ : 1000 lb



# 2.6 VOC RAPTOR BEDLINER HARDENER - UP0827 / UP4824

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>xylene (1330-20-7)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	100 lb
<b>Solvent naphtha (petroleum), light arom.,</b>	
Not listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>HEXAMETHYLENE DIISOCYANATE OLIGOMERS (28182-81-2)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

### 15.2. International regulations

#### CANADA

No additional information available

#### EU-Regulations

No additional information available

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 2 H225

Skin Irrit. 2 H315

Eye Irrit. 2 H319

Skin Sens. 1 H317

STOT SE 3 H335

STOT SE 3 H336

Full text of hazard classes and H-statements : see section 16

#### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

##### 15.2.2. National regulations

<b>ethylbenzene (100-41-4)</b>
Listed on IARC (International Agency for Research on Cancer)

### 15.3. US State regulations

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer, developmental and/or reproductive harm

<b>ethylbenzene (100-41-4)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
Yes	No	No	No	54

## SECTION 16: Other information

Other information : None.

# 2.6 VOC RAPTOR BEDLINER HARDENER - UP0827 / UP4824

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated exposure
H411	Toxic to aquatic life with long lasting effects

NFPA health hazard


: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard

: 2 - Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur.

NFPA reactivity

: 1 - Materials that in themselves are normally stable but can become unstable at elevated temperatures and pressures.



SDS US UPOL

*For professional use only.*

*The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at WWW.U-POL.COM.*